

DESCRIPTION

The M-633D is a stereo mixer equipped with 12 input channels (6 monaural inputs (*1) and 3 stereo inputs) and 6 output channels (2 monaural outputs, 1 stereo output, and 1 stereo recording output). It has 2 monaural channel and 1 stereo channel bus lines, allowing each input signal to be assigned to each bus line individually.

It features digital signal processing functions such as Automatic Resonance Control function (ARC (*2)), Feedback Suppressor function (FBS), Automatic Clipguard function (ACG), and Automatic Mute function (AUTO MUTE (*3)).

It performs advanced acoustic compensation by means of automatic processing without the use of an acoustic measuring instrument.

It can be mounted in an EIA component rack (1U size).

(*1) Selectable from microphone input, line input, and phantom power supply input independently for each input.

(*2) A function that automatically creates a sound field compensation filter (ARC filter) to improve sound clarity by measuring the inherent acoustic characteristics in architectural space.

(*3) AUTO MUTE is also called as Ducker.

SPECIFICATIONS


(*4) 0 dB = 1 V

Power Source	220 - 240 V AC, 50/60 Hz
Power Consumption	14 W
Frequency Response	20 Hz - 20 kHz
Sampling Frequency	48 kHz
Dynamic Range	90 dB or more (IHF-A weighted)
Distortion	0.03 % or less, 1 kHz, -10 dB(*4) input, 0 dB(*4) output (20 Hz - 20 kHz BPF)
Input	6 monaural input channels (MONO IN 1 - 6), selectable independently from 3 types of inputs below for each channel LINE : -10 dB(*4), 2.4 kΩ MIC : -46 dB(*4), 2.4 kΩ PHANTOM: -46 dB(*4), 2.4 kΩ supplies phantom power of +24 V DC, 10 mA electronically balanced Removable terminal block (3 pins), phone jack 3 stereo inputs (L, R) (STEREO IN 1 - 3) -10 dB(*4)/ 10 kΩ, RCA jack (STEREO IN 1 - 3), Stereo mini jack (ST IN 1)
Output	2 monaural output channels (MONO OUT 1, 2) 0 dB(*4) (applicable load: 1 kΩ or more), electronically balanced, removable terminal block (3 pins) 1 stereo output (L, R) channel (ST OUT L, R) 0 dB(*4) (applicable load: 1 kΩ or more), electronically balanced, removable terminal block (3 pins) 1 stereo recording output (L, R) channel (REC OUT L, R) -10 dB(*4) (applicable load: 1 kΩ or more), RCA jack
Bus Line	Monaural channel × 2, Stereo channel × 1
AD Converter	24 bits
DA Converter	24 bits
Signal Processing	
Automatic Resonance Control Function	3 output channels (each monaural output channel, stereo output L, R), independent settings for each channel, automatic creation of EQ curves (for sound field compensation) ARC measurement start switch × 1, Function ON/OFF check indicator × 1
Feedback Suppression Function	6 channels (each monaural input channel), independent settings for each channel Function ON/OFF switch × 6, Function ON/OFF check indicator × 6
Automatic Clipguard Function	6 channels (each monaural input channel), independent settings for each channel
Automatic Mute Function	Function ON/OFF switch × 1
Input Level Indicator	2-color LED indicator: Green (for appropriate level)/red (for peak level)
Output Level Indicator	2-color LED indicator: Green (for appropriate level)/red (for peak level)

SPECIFICATIONS

Finish	Panel: Aluminum, black, hairline Case: Precoated steel sheet, black, 30 % gloss
Dimensions	420 (W) × 44 (H) × 341.3 (D) mm (16.54" × 1.73" × 13.44")
Weight	4 kg (8.82 lb)
Accessories	Power cord (2 m (6.56 ft))1, Removable terminal plug (3 pins)10, Rack mounting bracket2, Machine screw (M3 × 8)6, Rack mounting screw (5 × 12)4

APPEARANCE




Rear View

Model	CE	CE-GB	CE-AU
Indication	CE	CE-GB	CE-AU
	50/60Hz	50/60Hz	50Hz
AC plug			
RCM	-	-	applicable

483.6 [19.04"]

466 [18.35"]


420 [16.54"]



Front View

31.8 [1.25"]

44 [1.73"]



Front View with a assign cover detached

341.3 [13.44"]

320 [12.6"]

20 [0.79"]

20 [0.79"]

22 [0.87"]

6-M3

Side View

UNIT: mm SCALE: 1/3